


AMFH series breadboards with active air isolation

High Performance breadboards incorporating air vibration isolation







- Incorporates unique air damped rolling diaphragm sub 2Hz isolators which remove up to 99 percent of vibrations
- A modular range of options allows you to configure tables to your own specifications
- Stainless steel version meets stringent cleanliness requirements and is resistant to almost all forms of chemical attack



AMD-FH-90x75



AMD-FH-75x75 with microscope



AMD-FH-90x75 with confocal laser microscope

Sound deadened table construction eliminates unwanted surface vibrations


Our range of active isolation breadboards allows you to build up systems on a bench with the advantage of a high performance isolation system being built into the breadboard. The air isolation effectively removes most removes most vibrations while combining excellent stability. The damped rolling diaphragm isolators have a low natural frequency of 2Hz which effectively isolates out vibrations above 6Hz well below the frequencies at which typical building vibrations begin to occur. A wide range of option includes: frames, guard rails, monitor arms, castors, stainless surface and silent air compressors.




Product Details

The AMFH platform series is supported by a wide range of options. These include a frame and a full size shelf that fits over the frame struts, a computer arm that is adjustable and can be placed on the right or left side at the back. Guard rails to protect against accidental knocks and an arm rest bar that is height adjustable and attaches to the front, which is used with gel arms rests. A range of castor feet is available and also a compact silent compressor, which supplies clean dry air to the table.







Specifications AMFH platforms

Dimensions (LxWxD) cm's Tables	40x50, 60x60,60x90 75x75, 90x75,120x75
Platform working height mm's	60
Load capacity	100kgs
Level adjustment (mm's)	+/-3mm
Surfaces	ferritic satin silicon stainless steel
Isolators	4off damped rolling diaphragm active air self-levelling
, Isolation performance 50Hz 100Hz	97 percent 99 percent

2Hz

Options

F01	Frame
F02	Frame shelf
F03	Platform guard
F04	Platform shelf
F06	Retractable castor feet
F08	Arm rest bar
F10	Monitor post
F15	Gel arm rest
F17	Keyboard shelf
F27	Active area worktop
C01	Silent compressor



Air supply

Natural frequency

5 bar (max 7) via 6mm push-fitting

Working temperature

-20 to +160 deg C